
SK700-II LPG IOD

An economical and stylish solution

- > Island orientation
- > Single grade
- > Minimal footprint



Product Specifications

The SK700-II LPG IOD is an entry-level single hose solution with island orientation, hose hook, single grade and minimal footprint.

Technical Specifications	Standard Features	Options
Hydraulics	LPG hydraulics with 1 or 2 meters Electronic meter calibration Break away coupling – Elaflex	Solenoid valve: two stage dual flow for pre-set Shear valve
Electronics	Pulser Calculator LCD display (back lit) Dead man push button	Emergency stop button Automatic Temperature Compensation (selected countries) Pre set keypad Computer head door alarm Bolt-on CRIND ready Communication protocol options Electromechanical totaliser
Mechanical	Housing – painted steel Frame – hot galvanized sheet metal Hose Management – internal hose connection CR LPG nozzle – T3 OPW Hose – Elaflex	Stainless steel hose column and hydraulic panels Livery options on request Types of nozzles on request Nozzle lock Hose management system: external hose with rope retract

Technical Characteristics & Performance

Environmental	Climate: Marine, tropical, industrial, polar Ambient temperature range: -20°C to +50°C (optional down to -25°C)
Meter characteristics	Displacement: 0,500L Maximum flow rate: 50L/min Minimum flow rate: 5L/min Accuracy within the flow range: ± 1% Maximum service pressure (operating pressure): 25 bar
Electrical	230V (+10%; -15%), 50Hz ± 2Hz

